

Sliding doors

The REHAU Perspektive 2200, high-performance sliding door offers superior operation and thermal efficiency, making it an excellent choice for upscale residential renovation and new construction projects. Designed to be offered as a knocked-down (KD) kit or as a fully assembled, mechanically joined frame in white or clay, and can be laminated with solid colors or wood-grain foils.



European saddle-rail sash design

Provides exceptionally smooth, low-friction operation and is easier to clean

Low-profile, aluminum-capped sloped sill

Offers unobstructed building entry with the durability of an anodized aluminum finish

6 in (152 mm) frame depth with integral nailing fin option

Allow for new and replace door applications

4 Internal sill drainage system

Achieves superior resistance to water leakage

5 Steel sash reinforcement

Creates superior structural rigidity, allowing for installation in light-commercial applications

6 13/8 in (35 mm) glazing channel

Accommodates triple glazing, increasing both energy efficiency and acoustical properties

Multiple configurations

Allow flexibility for X-O, O-X, O-X-O, O-O-X, X-O-O or O-X-X-O operation and dedicated fixed frame for sidelite and transom

8 Frame accessory grooves

Accept a variety of accessories such as brickmolds, extension jambs and mulling components

9 Multi-point locking system

Provides added security and product performance



For further details, visit na.rehau.com/2200