



IMA SCHELLING
GROUP



Novimat

The Novimat Concept and Systems range for highly efficient production

imaschelling.com

NOVIMAT R3 | L20

the throughfeed machine for quality, productivity
and flexibility

All the units of the Novimat are of solid design and have optimal motor power, which ensures excellent repeatability, a high utilization rate and a long life expectancy. The Novimat allows cost-efficient and reliable edgbanding using tape up to 3 mm and lippings up to 20 mm thick.



NOVIMAT
EN 06/2022



Energy-efficient production


Protection of the environment and energy efficiency are standard features of the Novimat series: Examples of this include the integrated standby mode, optimized extraction of the processing units, minimal usage of compressed air, and energy-efficient drive technology.

OVERVIEW




BASE FRAME

solid and rigid fabricated base frame



ICOS OPEN

the ideal controller for single machines and high-performance systems




MACHINE INFEED

for manual or automated workpiece infeeding




GLUING AREA

offers various processes for edge banding (also in combination)




EDGE MAGAZINE

with up to 24/48-station edges shafts (depending on the range)



CONTOUR MILLING UNIT

for a high-quality and aesthetic look for your products





COMPREHENSIVE
UNIT MODULES
FOR INDIVIDUAL
MACHINE EQUIPPING


DETAILS OF THE RANGE

Maximum flexibility and quality for a modern variety of materials

Using the single-sided automatic edge processing machine, both roll and strip material can be processed flexibly and to high quality in pass-through. Thanks to a wide variety of units for joining, edge gluing and edge post-processing, the machines of the Novimat range produce perfect results for an aesthetic look and perfect quality of your products.


CONTOUR MILLING UNIT (KFA)

- servo/linear system
- processing unit for the leading and trailing edge
- automatic/self-positioning of the milling tool along the profile
- large tracing roller of 140 mm diameter
- direct drive technology and low weight for dynamic performances and high cycle rates
- profile changeovers are possible in between the panel gap
- adaptive parameters for the processing of specific materials (e.g. with regard to lightweight materials, reduction of the tracing force)
- IMA-patent
- up to 4 profiles and chamfers in the outlet



CONTOUR TRIMMING UNIT (SKF)


- radius and chamfer milling
- manual positioning of the milling motor for chamfer milling (optional: NC adjustment)
- milling motor with quick-change system for easy setting up for various radii



MACHINING RANGE

A WORKPIECE FEEDING AND HANDLING


Efficient and precise feeding of workpieces and in panel return conveying systems for one-man operation for optimal structuring of the vicinity of the machine.



Infeed table small




21.5" wide monitor with touch screen keyboard and mouse operation




Servo infeed and détente stop system

1 JOINING


- two-station, 3-station or 4-station joining matched for perfect joining results with your materials
- tool diameters of 125 or 150 mm possible
- also with hydraulic pickup



Two-station joint milling




Four-station joint milling



2 GLUING AREA

Novimat R3

- with quick-lock glue applicator
- for coil material up to 3 mm
- Laser Edging and/or conventional gluing
- melting system for all current melt-type adhesives




Edge banding unit with 12-coil magazine

Novimat L20

- with Quick-lock glue applicator
- for coil material up to 3 mm and solid wood strips up to 20 mm
- conventional gluing



Laser unit with 12-fold edge magazine




Laser Edging diode laser


3 POST-PROCESSING

End trimming, Milling, contour trimming


- end trimming unit for straight and chamfer trimming
- milling unit (pre-milling)
- profile milling unit or multi-profile milling unit
- contour milling unit (KFA)
- contour trimming unit (SKF)




End trimming unit




Pre-/flush milling unit




Multi-profile milling unit



Contour milling unit KFA x20



Contour milling unit KFA x30




Contour trimming unit (SKF)


4 FINE-FINISH AND GROOVING

planing, buffing, milling


- profile scraper or Multi-profile scraper unit
- flat scraper unit
- buffing unit oscillating
- corner buffing unit
- buffing unit with 2 or 4 motors
- smoothing unit
- grooving unit
- sanding unit
- profile sanding units (top + bottom)




Multi-profile scraper unit
Flat scraper unit
Buffing unit with 4 motors



Multi-profile scraper unit
Flat scraper unit
Buffing unit with 2 motors



Corner buffing unit



Grooving unit


INTEGRATION OPPORTUNITIES

Depending on the production work flow and degree of automation of your production, the machines of the Novimat Concept or Systems range can be equipped both with infeed systems and panel return systems. Operation is thus made easier and more efficient. It is also possible to directly connect the machines to the upstream and downstream process steps with no problems.



FEEDBACK SERIES

Work piece return feed systems in many configurations for various sizes of work pieces and cycle times.



PERFORMANCE.ONE SOLUTIONS

partially automated solution for efficient batch size 1 production

- modular, future-proof machine concept of IMA Schelling panel sizing and edge processing machines
- modern production technology with simple operation
- high quality production with proven IMA Schelling unit technology
- training options for your operators to ensure efficient production



ICOS OPEN - HIGHEST EASE OF USE


The ICOS Open PC-controller guarantees the highest performance concerning the optimization of productivity results. The controller guarantees the perfect information flow between operator and machine therefore providing optimal conditions for a smooth production process. The ICOS Open operator system combines the control functionality for the machine and the individual working units. The clearly laid out screen menu is accomplished by icons. The individual processing steps are visually displayed in pictograms. Current machine data (i.e. optimum glue temperature) is imported into the icons.

ICOS OPEN OVERVIEW

- modern 21,5" wide-screen machine controller
- touch, keyboard or mouse
- Windows® operating system
- two hard drives for additional peace of mind
- uninterrupted Power Supply
- job list function
- program management for main- and sub-programs
- tooling and edgeband data management
- error display in clear text
- MDE
- prepared for tele-service (controls prepared for later addition of IMA Service Portal)

OPTIONAL

- bar code control
- IMA Maintenance Manager
- IMA Serviceportal
- Remote service via IMA Service Portal with the following functionality
 - service ticket
 - remote diagnostics
- and much more





SERVICE PLATFORM ZIMBA

The ZIMBA service platform is an agreement with which we shape our relationship: 100% transparency, 100% modularity and almost 100% efficiency - from the first to the last production day of your plant.

In addition to the classic ticket and hotline modules, further services are available via ZIMBA that extend the production quality and efficiency as well as the service life of your IMA Schelling machines and systems.

ZIMBA.PORTAL



is the entry into the ZIMBA world and includes:

- Documentation
- Administration
- User management & administration
- Security Updates
- Installations & connection fee
- Ongoing updates and data connection checks

ZIMBA.TICKET



offers fast and qualified support through the ticket system and spare parts management. It includes:

- 24h online ticket system
- Telephone accessibility
- E-parts
- Digital machine documentation
- Ticket history
- Remote Assist

ZIMBA.MAINTENANCE




is the time-based maintenance manager. Maintenance can be scheduled & documented on time and assigned to staff. This includes:

- Automatic maintenance messages
- Automatically generated knowledge articles for the maintenance messages
- Creation of maintenance lists
- Documentation of the maintenance carried out


TECHNICAL DATA

	R3	L20
MACHINE		
Track speed [m/min] (the max. track speed rate depends on the end trimming and contour trimming units)	6 - 30 m/min.	
Fixed panel overhang from the chain track (including the edging)	38 mm	38 mm (with edging thickness 0,3 - 8 mm)
WORKPIECE		
Panel thickness	min. 8 mm max. 60 mm	
Panel length	min. 150 mm	
Panel width	min. 65 mm	min. 65 mm (with edging thickness 0,4 - 3 mm)
EDGE TAPE		
Tape height	min. 14 mm max. 65 mm	
Tape thickness	min. 0,4 mm max. 3 mm	min. 0,4 mm max. 20 mm
POWER SUPPLY + COMPRESSED AIR SUPPLY		
Power supply	3/ N, 400 V +5/ -10 % 50 Hz	
Control voltage	24 V	
Compressed air	7 bar	

EDGING MATERIAL: COILS




EDGING MATERIAL: SOLID WOOD LIPPINGS



SMALLEST PANEL (LENGTH WISE PROCESSING):

All dimensions in mm [inch].

All equipment offered is made to metric standards. Dimensions shown in English measure are approximate and for comparison purposes only.



The IMA Schelling Group is a reliable partner for implementing of sophisticated system solutions.
The demands of our customers are a daily challenge to us, our know-how
and creativity! We work with you to develop innovative and unique solutions for wood processing.

www.imaschelling.com

Modifications and mistakes reserved. Illustrations are approximate. Subject to technical modifications and mendments and to further developments. The offer, respectively the order confirmation is relevant in either case! The picture of the machine could have been taken without complete protection devices. The protection device is part of the scope of delivery. Photos could also be options, not being part of the scope of delivery and are not binding in detail.



IMA SCHELLING
GROUP