

RAUAQUA T-FLEX

Multi-layer hose for use in drinking water and food applications.
The RAUAQUA T-FLEX meets the strict requirements of the UBA for products in contact with drinking water. Tested according to KTW-BWGL (Annex E) for cold and hot water and DIN EN 16421:2015-05.



- **Highly flexible**
- Absolutely opaque, therefore counteracts the formation of dangerous microbes and algae
- Durable marking due to embossing
- Compatible with GK coupling and conical screw connection
- Homogeneous connection
- UV-resistant and resistant to standard cleaning and disinfection agents (based on DVGW W319 and W291)
- Temperature range: -30 °C bis +70 °C



**New: An
Alternative
to the rubber
hose**

Mat-No.	Delivery format	Working pressure bar (at 20 °C)	EAN code (D)
10049011001	12.8 mm (1/2") 25 m coil	15	40 64299 949200
10049011002	12.8 mm (1/2") 50 m coil	15	40 64299 949217
10049021001	19.0 mm (3/4") 25 m coil	15	40 64299 949224
10049021002	19.0 mm (3/4") 50 m coil	15	40 64299 949231
10049031001	25.0 mm (1") 25 m coil	10	40 67936 119608
10049031002	25.0 mm (1") 50 m coil	10	40 67936 119615