

PRODUCT SUBMITTAL 410

Product: Automatic By-pass Valve (AVDO)

Date: 09-January-09



Article No.	Description
260517	1/2" C Female (Sweat) Pressure Bypass Valve
260527	3/4" C Female (Sweat) Pressure Bypass Valve
267987	1" MPT Pressure Bypass Valve

TECHNICAL DESCRIPTION

Maximum working temperature:	248°F (120°C)
Maximum acceptable working pressure:	145 psi (10 bar)
Maximum differential pressure:	7.25 psi (0.5 Bar)
Setting Range:	0.725-7.25 psi (0.05-0.5 Bar)
Maximum leakage when closed:	0.22 GPM (0.05 m ³ /h)
Approximate Envelope Dimensions:	260517 (1/2") 4.76" x 3.50" x 1.85" (121 x 113 x 47mm) 260527 (3/4") 5.39" x 4.49" x 1.85" (137 x 114 x 47mm) 267987 (1") 7.00" x 4.69" x 1.85" (178 x 119 x 47mm)

FUNCTIONAL DESCRIPTION

Pressure differential bypass valves divert excess flow when one circulator pump is used with multiple zones, reducing wear on the pump, avoiding noise problems in the control valves, and allowing more stable temperature control. Applications include PRO-BALANCE® manifolds using manifold valve actuators. Valves are pressure-adjustable. Connections (union ends) are to copper pipe for 1/2" and 3/4" valves. The 1" valve is supplied with 1" MPT union ends.

For complete technical performance specifications, please refer to Danfoss Data Sheet VD.55.K6.22 (1/1998).

For updates to this publication, visit na.rehau.com/resourcecenter

The information contained herein is believed to be reliable, but no representations, guarantees or warranties of any kind are made as to its accuracy, suitability for particular applications or the results to be obtained therefrom. Before using, the user will determine suitability of the information for user's intended use and shall assume all risk and liability in connection therewith. To the extent permitted by law, REHAU EXPRESSLY DISCLAIMS ALL IMPLIED WARRANTIES, INCLUDING BUT NOT LIMITED TO, ANY IMPLIED WARRANTIES OF MERCHANTABILITY OR OF FITNESS FOR A PARTICULAR PURPOSE.

© REHAU Incorporated 2009