

Properties	Test Method	Property or attribute	Unit	Result
SURFACE QUALITY				
Surface Quality	Dents and Protrusions	0.8mm size or smaller	QTY/m ²	8
		Greater than 0.8mm size	QTY/m ²	0
DIMENSIONAL TOLERANCES				
Panel Dimensional Tolerances		Thickness tolerance	mm	19.8 ± 0.3
		Length and width	mm	± 5
GENERAL PROPERTIES				
Scratch Resistance	DIN 55656	Scratch with 1mm Hardness Pen	N	2
	DIN 55656	Scratch with Steel Disk	N	5
Micro-scratch Resistance	DIN CEN TS 16611	Appearance	Rating	5
Stain Resistance	EN 12720:2009	Appearance	Rating	≥ 4
UV Light Resistance	EN 4892-2:2013	Appearance	Grey Scale 6	≥ 4
Gloss Level		Gloss level measured at 60 degrees	Gloss units	3 ± 2
Color	White	Appearance	Δ E	Max 0.5
	Greys & Black	Appearance	Δ E	Max 0.8
	Bright Colors	Appearance	Δ E	Max 1.0
NOTES				
Storage Conditions: Product should be kept at room temperature between 59F-77F with relative humidity between 30%-70%. Do not expose to direct sunlight and humidity.				